



Investigating physics learning with layered student interaction networks Combining time and mode of interaction



Bruun, Jesper; Traxler, Adrienne

Publication date:
2016

Document version
Peer reviewed version

Document license:
[GNU GPL](#)

Citation for published version (APA):
Bruun, J., & Traxler, A. (2016). *Investigating physics learning with layered student interaction networks: Combining time and mode of interaction*. Poster session presented at Physics Education Research 2016, Sacramento, United States.



Investigating physics learning with layered student interaction networks: Combining time and modes of interaction

Jesper Bruun, University of Copenhagen and Adrienne Traxler, Wright State University

1. Interaction in layered networks

Centrality in student interaction networks (SINs) can be linked to variables like grades [1], persistence [2], and participation [3]. Recent efforts in the field of network science have been done to investigate layered - or multiplex - networks as mathematical objects [4]. These networks can be explored via centrality measures, which then have to be modified to suit layered networks. In student interaction networks [1], a node represents aspects of a student, and links represent aspects of student interactions. Using longitudinal self-reported interactions from Danish university students, this study investigates how target entropy [5,1] and page-rank [6,7] are affected when we take time and modes of interaction into account. We present our preliminary models and results and outline our future work in this area.




Figure 1: Layered networks. The leftmost figure shows sample student interaction network layers for one week. A student potentially has a presence in each layer depending on the connections in that layer. The rightmost figure shows that layered networks can also be understood as a time sequence.

2. Models of interaction and engagement with categories and time

The analysis is based on *problem solving* (PS) and *concept discussion* (CD) SINs. We use the same dataset as in [1] and focus on PS and CD interactions. For each week, students have indicated with whom they remember having discussed problem solving and concepts in physics respectively.

Pagerank time model and category model

In a layered network, a random walker move both within and between layers [6,7]. The rank of a given node is the percentage of times that node is visited by the random walker.

Layered category networks can be seen to model modelling how individuals may engage with different kinds of knowledge and/or practices.

Layered time networks within a single category allow us to model individuals varying engagement with knowledge and/or practices.

Target entropy time model

Target entropy can be seen to model how likely a student is to engage with, for example, new ideas, new ways of doing or being, or concepts - here modelled as “messages”. With our time model, we introduce the idea that a student might not only engage with other students but also has a memory of previous weeks.

Target entropy of node i

$$T_i = \sum_{j \neq i, t_{t-1}} c_{ji} \log_2(c_{ji})$$

Fraction of “messages” from node j to node i

$$c_{ji} = \frac{n_{ji}(t)}{M_i^{tot}(t)}$$

Total “messages” to node i at time t . δ is a memory-effect.

$$\hat{M}_i^{tot}(t) = M_i^{tot}(t) + \delta M_i^{tot}(t-1)$$




Figure 2: Illustration of our time model for target entropy.

3. Preliminary results and ideas for next steps

We use the correlations pagerank~PS,CD and target entropy~CD [1] as benchmarks. For each model we calculate the layered centrality and compare with the corresponding benchmark. We found that PageRank on the agglomerated PS-CD layered network did worse than the benchmark for both CD or PS networks.




Figure 3: How multilayer pagerank compares to the benchmark for PS SINs. Numbers on x-axis refer to combinations of weeks

Place paper with graph here

Figure 4: How target entropy time model compares to the benchmark for CD SINs. Numbers on x-axis refer to different settings of parameter δ .

Next steps

- Try out other models and combinations for memory and layered models
- Extend analysis to other cohorts
- Investigate layered networks with respect to student communities
- Use records of student course completion as they are registered at UCPH

Selected Literature

- [1] Bruun, J., & Brewe, E. (2013). Talking and learning physics: Predicting future grades from network measures and Force Concept Inventory pretest scores. *Physical Review Special Topics-Physics Education Research*, 9(2), 020109.
- [2] Forsman, J. (2015). Complexity Theory and Physics Education Research: The Case of Student Retention in Physics and Related Degree Programmes. PhD thesis. University of Uppsala.
- [3] Brewe, E., Kramer, L., & Sawtelle, V. (2012). Investigating student communities with network analysis of interactions in a physics learning center. *Physical Review Special Topics-Physics Education Research*, 8(1), 010101.
- [4] Kivelä, M., Arenas, A., Barthélemy, M., Gleeson, J. P., Moreno, Y., & Porter, M. A. (2014). Multilayer networks. *Journal of complex networks*, 2(3), 203-271.
- [5] Sneppen, K., Trusina, A., & Rosvall, M. (2005). Hide-and-seek on complex networks. *EPL (Europhysics Letters)*, 69(5), 853.
- [6] Brin, S., & Page, L. (2012). Reprint of: The anatomy of a large-scale hypertextual web search engine. *Computer networks*, 56(18), 3825-3833.
- [7] De Domenico, M., Lancichinetti, A., Arenas, A., & Rosvall, M. (2015). Identifying modular flows on multilayer networks reveals highly overlapping organization in interconnected systems. *Physical Review X*, 5(1), 011027.

Contact

Jesper Bruun
Assistant Professor
jbruun@ind.ku.dk
Department of Science Education
Faculty of Science
University of Copenhagen

Adrienne Traxler
Assistant Professor
adrienne.traxler@wright.edu
Department of Physics
Wright State University